

We're a **big** part of your business



## MC 750-15W Wheel Conveyor

The ideal solution for stockpiling materials from static or mobile screens

**Please contact** Garth Taylor on 0274 960 406.

[www.mimico.co.nz](http://www.mimico.co.nz)

Freephone **0800 806 464** | E-mail [enquiries@mimico.co.nz](mailto:enquiries@mimico.co.nz) | Auckland, Matamata, Christchurch

Our brands



**metso**

**KOBELCO**



MATAMATA INDUSTRIAL MACHINERY IMPORTS LTD

# MC 750-15W Wheel Conveyor

## Heavy Duty Construction

Constructed from 5mm thick MS plate designed in 300mm deep section to give added stability and use in heavy duty applications.

## Conveyor

The conveyor is constructed in 2 sections, the tail section includes a generous feed hopper and the head section includes the conveyor drive, consisting of either a Sauer-Danfoss hydraulic motor or a Nord 7.5kw geared motor connected to a rubber lagged drive pulley.

## Undercarriage

The undercarriage consists of an adjustable support trestle arrangement, mounted on a single axle with 2 No. 11.5/80-15.3 flotation wheels for added mobility. The wheels can be manually rotated through 90° to provide a radial function, increasing the stockpile capability of the conveyor.

## Head Folding

The folding mechanism of the conveyor head section allows for quick site set up and provides a flexible approach to transport of the unit.

## Tail Section

The tail section consists of a generous 2m<sup>3</sup> capacity Reception Hopper, designed to accept material from a chute or a loading shovel. The tail section includes a self cleaning tail pulley and closely fitted trough rollers under the reception area. The tail section is complete with a ballast box and radial pivot.

## Emergency Stop System

Every MC750-15W conveyor is equipped from the factory with an emergency stop system that will render the plant inoperable when activated, providing added safety for the operator.

## Standard Features

Wheel Axle and Tow Bar.  
Choice of Hydraulic or Electric Drive.  
750mm (30") wide 3 ply belt.  
Folding on Head Section.  
Manual Raise and Lower from 10 to 26°.

## Options

Hydraulic Raise and Lower; Heavy Duty Belt;  
Chevron Belt; Impact Bars under Feed Point;  
Conveyor Belt Variable Speed Control; PVC covers;  
Galvanised Steel Covers.

## Specifications

Operational length: 15 metres.  
Operational height: 6.5 metres.  
Loading height: 1.2 – 3.4 metres.  
Transport width: 2.25 metres.  
Transport height: 2.5 metres.  
Transport length: 12.2 metres.  
Total weight: 3450 kg.



**Distributed in New Zealand by MIMICO.**

[www.mimico.co.nz](http://www.mimico.co.nz)

Freephone 0800 806 464 | E-mail [enquiries@mimico.co.nz](mailto:enquiries@mimico.co.nz) | Auckland, Matamata, Christchurch

Our brands  **metso**  **KOBELCO**  **ZF**  **Atlas Copco**

**MIMICO**®

MATAMATA INDUSTRIAL MACHINERY IMPORTS LTD